

# Self-Propelled Articulating Booms

7X<sup>™</sup>-135/70

### **Features**

## Standard Features

#### Measurements

- 43.15 m (141 ft) working height
- 21.26 m (69 ft 9 in) horizontal reach
- 23.01 m (75 ft 6 in) up and over clearance
- Up to 272 kg (600 lbs) lift capacity

#### **Productivity**

- Xchassis<sup>™</sup> extendable axles
- 3.66 to 6.10 m (12 to 20 ft) Jib-Extend™
- Self-levelling platform
- Hydraulic platform rotation
- Thumb rocker steering
- Proportional joystick controls
- On board full diagnostics and engine monitoring display
- Hvdraulic oil cooler
- Drive enable
- AC power cord to platform
- Horn
- Hour meter
- Tilt alarm
- · Descent, motion, & travel alarms
- Flashing beacon
- 360° continuous turntable rotation
- Four wheel high angle steer
- Four steering modes: front, rear, crab and coordinated
- Four wheel brakes
- Full-time positive traction 4WD
- · Adjustable foot switch timeout
- Two speed wheel motors
- · Configurable controls to limit lift height to 27.74 m (91 ft)
- Engine status display
- Certified load sensor

#### Power

- 12 V DC auxiliary power
- Engine protection package
- Deutz intake air heater
- Swing out engine tray

#### Easily Configured To Meet Your Needs

#### **Platform Options**

- Steel 2.44 m (8 ft) (standard)
- Steel 1.83 m (6 ft)
- Steel 2.44 m (8 ft) tri-entry

3.66 to 6.10 m (12 to 20 ft) Jib-Extend™

#### **Engine Options**

- Deutz turbo diesel, 55 kW (74 hp)
- Perkins turbo diesel, 55 kW (74 hp)

#### Drive/Steer

- 4 x 4 (standard)
- 4 wheel steer (standard)

#### Tyre Options

- Extra-wide rough terrain foam-filled (standard)
- Solid rough terrain tyres



#### **Options & Accessories**

#### **Productivity Options**

- Platform top auxiliary rail
- Air line to platform
- Power to platform (incl. plug, socket and ground fault interrupt leakage on
- Work lights package (2 on chassis, 2 on platform)
- Dual axis joystick steering
- Weld leads to platform (2)
- Biodegradable hydraulic oil (2)
- Aircraft protection kit (1,2): platform foam padding and platform disable system
- Hostile environment kit (2): cylinder bellows, boom wiper seals, platform and ground control box covers
- Deluxe hostile environment kit (2) adds. to basic kit center turntable shield, ring gear guard, tail pipe guard, engine cover flaps and air pre-cleaner
- Track & Trace (3) (GPS unit providing machine location & operating information)
- · Lockable platform control box covers
- Tool trav
- Operator Protective Structure
- Operator Protective Alarm

#### **Power Options**

- Deutz V-Belt Generator kit (110V/220V) (1)
- Diesel air intake pre-cleaner (2)
- Diesel catalytic scrubber muffler (1,2)
- Low temperature cut-out module
- Engine heater option (1)
- · Refinery kit with spark arrestor and electric or mechanical Chalwyn valve (1)

### **United Kinadom**

02/14 Part No. B109366UK

Riihikuja 3

01720 Vantaa

The Maltings, Wharf Road, Grantham NG31 6BH, T: +44 800 988 3739 (toll free), Fax +44 (0)1476 584334, Email AWP-InfoEurope@terex.com Visit www.genielift.co.uk/locations to view our global locations list.

#### Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico · Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Effective Date: February, 2014. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise actirresponsibly may result in serious injury and the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise actirresponsibly may result in serious injury and the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise actirresponsibly may result in serious injury and the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise actirresponsibly may result in serious injury and the properties of the propor death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2014 Terex Corporation. www.genielift.me

Simeri Oy Myynti: +358 400 363 526 info@simeri.fi

www.simeri.fi

Huolto: +358 400 514 374 Varaosat: +358 400 997 949

www.genielift.co.uk

<sup>(1)</sup> Available on selected models only. See your Genie representative for further information.

<sup>(2)</sup> Factory-fit option only

<sup>(3)</sup> Includes a first 2 years subscription