


## **SPECIFICATIONS**

Size	Metric	British
Max. Working Height <b>A</b>	10.00m	32ft 10in
Max. Platform Height <b>B</b>	8.00m	26ft 3in
Overall Length <b>©</b>	2.48m	8ft 2in
Overall Width <b>(</b>	1.15m	3ft 9in
Overall Height(Rails Up)	2.36m	7ft 9in
Overall Height(Rails Down)	1.83m	6ft
Platform Size(Length×Width)	2.27m×1.12m	7ft 5in×3ft 8in
Platform Extension Size <b>G</b>	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase <b>(</b>	1.87m	6ft 2in
Turning Radius(Inside/Outside)	0m/2.20m	0in/7ft 3in
Tyres	φ381×127mm	φ381×127mm

Performance		
S.W.L	450kg	992lb
S.W.L On Extension	113kg	249lb
Max. Occupants	2	2
Gradeability	25%	25%
Travel Speed(Stowed)	5.0km/h	3.10mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	34/30sec	34/30sec

Weight		
Overall Weight(Lead-acid Battery)	2710kg	5974lb
Overall Weight(Lithium Battery)	2650kg	5842lb

Power		
Hydraulic Tank	20L	5.3gal
Battery	24V/185Ah	24V/185Ah
Charger	24V/30A	24V/30A
Driving Motor	2×24VAC/0.87kW	2×24VAC/0.87kW
Lifting Motor	24VAC/3.50kW	24VAC/3.50kW









## **FEATURES**

## **Standard Items**

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- Manual Brake Release
- · Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



## ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











